

Technical Data Sheet.

Permacron® Spot Repair Hardener 3045 extra fast

Application

Permacron®Spot Repair Hardener 3045 extra fast is a polyisocyanate hardener for two-pack products from our “2K-Acryl-System”.

Data

It is used for spot repairs at normal and low temperatures and makes for a quick refinish when used in combination with Permacron®Automotive Top Coat Series 257, Permacron®clear coats and all Permacron®/Permasolid®2K acrylic surfacers.

Storage

This product is for the professional painting of vehicles only.



Application



Possible base materials:

Permacron®Automotive Top Coat Series 257
Permacron®2K clear coat
Permacron®/Permasolid®2K acrylic surfacer

Fields of application:

Suitable for spot repairs at normal and low temperatures.

Mixing ratio:



See Technical Data Sheet of the respective base materials.

Data



Specific weight:

approx. 0.95 g/cm³

Flash point:

above +10°C

VOC value:

636 g/l

Storage



Guaranteed shelf life:

6 months in sealed original containers

Storage conditions:



Do not store in damp conditions.



After use, replace container lid immediately, ensuring an airtight seal.

The employed tests comply with state-of-the-art technology regarding methods and accuracy. The quoted measuring results do not constitute a legal warranty of specific product features or of the products' suitability for a specific purpose. Warning remarks on the labels must be observed. Any existing industrial property rights must be considered. According to our general terms and conditions of domestic and export sale, we warrant that our products are in the condition specified in the contract.



SPIES HECKER GMBH
Fritz-Hecker-Str. 47 - 107 • D - 50968 Köln
Phone (0)2 21 - 37 06-06 • Fax (0)2 21 - 37 06-410

