

Technical Data Sheet.

Permanent Silicone Remover 7010 Permanal® Silicone Remover 7799

Use

Permanent Silicone Remover 7010 is a slowly evaporating organic solvent mixture, and Permanal® Silicone Remover 7799 a fast evaporating mixture used primarily to remove oil and grease residues.

Data

Storage

These products are used for cleaning sanded old or original finishes and surfaces coated with primer or surfacer which have been subsequently sanded.

This product is for the professional painting of vehicles only.



VR Technical Data Sheet No. 730.0/10/2003-GB

Use



As silicone remover:

For cleaning surfaces prior to applying primers, surfacers or top coats.

Application

Apply Permanent Silicone Remover 7010 or Permanual® Silicone Remover 7799 with a spray bottle or clean cloth.

Wipe dry with a clean cloth before the silicone remover evaporates.

Special notes:

1. Allow cleaned surfaces to dry completely before recoating.
2. Do not allow the silicone remover to dry on the surface.
3. This product is not suitable for cleaning spray guns or tools
4. Always use a clean cloth.
5. Heavily soiled parts must be cleaned twice.

Data



	Permanent Silicone Remover 7010	Permanual® Silicone Remover 7799
Specific weight:	0.75 g/cm ³	0.74 g/cm ³
Flash point:	+26°C	-5°C
VOC value:	747 g/l	745 g/l

Storage



Guaranteed shelf life:

6 months in sealed original containers

The employed tests comply with state-of-the-art technology regarding methods and accuracy. The quoted measuring results do not constitute a legal warranty of specific product features or of the products' suitability for a specific purpose. Warning remarks on the labels must be observed. Any existing industrial property rights must be considered. According to our general terms and conditions of domestic and export sale, we warrant that our products are in the condition specified in the contract.



SPIES HECKER GMBH
Fritz-Hecker-Str. 47 - 107 · D - 50968 Köln
Phone (0)2 21 - 37 06-06 · Fax (0)2 21 - 37 06-410